

PIATTAFORMA	DISK DRIVE	EMULATORE	ACCELERATORE	DIMENSIONE BLOCCO				MEDIA	RATIO	EFFETTIVO
				256	512	1024	2048			
atari	sd	ALTIRRA	SIO2SD	7111,00	10666,00	19555,33	26311,00	15910,83	960	15274,4
atari	dd	ALTIRRA	SIO2SD	7111,00	10666,00	19555,33	26311,00	15910,83	960	15274,4
plus4	c1551	YAPE 1.1.8	emulazione IEC	4444,33	4042,00			4243,17	960	4073,44
c128	c1541	VICE 3.5	jiffyDOS 6.01	2285,00	2293,00	2666,00	7578,00	3705,50	960	3557,28
c128	c1541-II	VICE 3.5	jiffyDOS 6.01	2285,00	2293,00	2666,00	7578,00	3705,50	960	3557,28
c128	c1581	VICE 3.5	jiffyDOS 6.01	2666,00	3221,33	3430,33	3460,67	3194,58	960	3066,8
c64	c1541	VICE 3.5	jiffyDOS 6.01	3200,00	2909,00	3098,00	3028,33	3058,83	960	2936,48
c64	c1541-II	VICE 3.5	jiffyDOS 6.01	3200,00	2909,00	3098,00	3028,33	3058,83	960	2936,48
c128	c1571	VICE 3.5	jiffyDOS 6.01	2666,00	2775,67	2743,33	2762,33	2736,83	960	2627,36
plus4	c1551	YAPE 1.1.8		1056,67	910,67	891,67	910,67	942,42	960	904,72
c64	c1571	VICE 3.5	jiffyDOS 6.01	760,00	627,33	654,67	674,67	679,17	960	652
c64	c1581	VICE 3.5	jiffyDOS 6.01	661,67	641,00	628,00	623,33	638,50	960	612,96

